

SKU: IPC1-100-8-m256-12\_5-X-Thinux-0

Thinvent® IPC1: Engineered for Peak Industrial Performance and Ultimate Reliability.









## Processing

_	
Cores	4
Max Frequency	3.4 GHz
Cache	6 MB
Main Memory	8 GB
SSD Storage	256 GB
Display	
HDMI	1
VGA	1
Audio	
Speaker Out	1
Mic In	1
Front Speaker Out	1
Front Mic In	1
Connectivity	
USB 3.2 Gen 2	2
USB 3.2 Gen 1	1
USB C	1
Front USB 2.0	4

## Networking

Ethernet	1000 Mbps		
Power			
DC Voltage	12 Volts		
DC Current	5 Amps		
Power Input	100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum		
Cable Length	2 Metre		

### Environmental

Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	RoHS, ISO, BIS
Physical	

Physical	
Dimensions	199.5mm × 181.5mm × 34.5mm
Housing Material	Aluminium
Housing Finish	Powder Coated Base, Anodised Cover
Housing Colour	Black

### Accessories

VESA Mount 1

# Operating System

Operating System	Thinvent® Thinux™ Embedded Linux
OS Features	Chromium and Mozilla Firefox browsers.
	RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.
	Browser based remote management. VNC shadowing.
	Java, Python and glibc based location application support.
	LibreOffice and PDF viewer.
	Multimedia player with MPEG4 support.
	SIP video and voice over IP.

